

60 AG series

x60x15mm



General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Plastic(UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

Model	*Bearing System	Rated Voltage	Operating Voltage Range	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
Part NO.	B / S / F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
AGE06015_12J	B / S	12	7.0~13.2	0.06	3000	0.43	15.0	2.3	0.09	24.0	44
AGE06015_12L	B / S	12	7.0~13.2	0.08	3500	0.54	19.0	3.5	0.14	29.0	44
AGE06015_12M	B / S	12	7.0~13.2	0.10	4000	0.62	21.7	4.1	0.16	32.0	44
AGE06015_24M	B / S	24	14.0~26.4	0.05	4000	0.62	21.7	4.1	0.16	32.0	44
AGE06015_12H	B / S	12	7.0~13.2	0.12	4500	0.65	23.1	4.6	0.18	35.0	44
AGE06015_24H	B / S	24	14.0~26.4	0.08	4500	0.65	23.1	4.6	0.18	35.0	44
AGE06015_12U	B / S	12	7.0~13.2	0.17	5000	0.75	26.5	5.7	0.23	37.0	44
AGE06015_24U	B / S	24	14.0~26.4	0.11	5000	0.75	26.5	5.7	0.23	37.0	44

*Bearing system B: Two Ball Bearing F: Fluid Bearing S: Sleeve Bearing

