


∅ 133 BG series

x91mm



■ General Specifications

- Motor : 8 Poles brushless DC motor
- Frame & Impeller : Al die casting & plastic

■ Major Characteristic Parameters

Model	Bearing System	Rated Voltage	Operating Voltage Range	Rated Current	Rated Speed	Maximum Air Flow	Maximum Static Pressure	Sound Level	Weight		
Part NO.	B / S / F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	Kg
BGN13391B24U	B	24	18.0~28.0	1.6	4000	6.00	212	36.8	1.45	65	0.74
BGN13391B48U	B	48	36.0~56.0	0.8	4000	6.00	212	36.8	1.45	65	0.74
BGN13391B48S	B	48	36.0~56.0	1.3	4500	7.00	247	41.5	1.63	70	0.74

∅ 175 BG series

x69mm



■ General Specifications

- Motor : 8 Poles brushless DC motor
- Frame & Impeller : Al die casting & plastic

■ Major Characteristic Parameters

Model	Bearing System	Rated Voltage	Operating Voltage Range	Rated Current	Rated Speed	Maximum Air Flow	Maximum Static Pressure	Sound Level	Weight		
Part NO.	B / S / F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	Kg
BGN17569B24H	B	24	18.0~28.0	1.5	3300	9.35	330	38.1	1.50	63	0.73
BGN17569B48H	B	48	36.0~56.0	1.2	3300	9.35	330	38.1	1.50	63	0.73
BGN17569B48U	B	48	36.0~56.0	1.2	4200	11.55	408	63.0	2.48	72	0.73